

MAINTENANCE SCHEDULE 1999 to 2002 DISCOVERY Series II

Owner's N		 						_	
Date:	Mileage			RO#	f:				
MAINTENANCE	TIME (Months)	6	12	18	24	30	36	42	48
INTERVAL	MILES (Thousands)	7.5	15	22.5	30	37.5	45	52.5	60
	KILOMETERS (Thousands)	12	24	36	48	60	72	84	96
VEHICLE EXTERIO	R								
Add 16 oz Land Ro	over Fuel Conditioner (LRN5010)			□	О				
Inspect wiper blade	es								
Lubricate door lock									
Lubricate hood late	ch and safety catch, fuel door hinges								
Replace Alarm har	ndset batteries				□				
VEHICLE INTERIOR	र								
Check parking bral	ke (Adjust if necessary)				О				
Check seat belts									
UNDER HOOD									
Inspect coolant hos	 ses						0		
Inspect radiator an	d AC condenser								
	ing fluid level/ACE fluid level								
Clean battery and									
Inspect serpentine	drive belt				□				
Replace serpentine	e drive belt								
Check brake fluid level									
Change brake fluid			1						
★ Replace air-clea	ner element								
Change engine coo	olant								
★ Replace spark p	lugs								
UNDER VEHICLE									
★ Change engine of the control of the con	oil and replace filter								
Perform body corro	osion warranty inspection								
Inspect tire pressu	res, condition and tread depth								
Inspect brake pads, calipers and discs									
Inspect exhaust sy	stem and heat shields				□				
Inspect brake lines					□				
Lubricate drive sha	afts and U-joints								
Inspect steering ro	ds, joints and dust covers								
Inspect shock abso	orbers								
Inspect suspension links and mountings									
Check trailer hitch	attachment bolts for tightness								
Inspect wheel speed sensor and height sensor wiring									
Inspect fuel and hydraulic lines									
Change transfer gearbox oil									
Change transmission fluid									
Replace transmission fluid filter (One-time only)									
Check front and rear axle oil level									
Change front and r									
	transmission mounts								
Check steering box									
Service SLS filter (
Service ACE filter						<u>-</u>			_
Record performand	ce of Service in Passport to Service booklet								

* REQUIRED EMISSION MAINTENANCE

SUPPLEMENTARY RESTRAINT SYSTEM (SRS): The AIR BAGS in the SRS must be replaced EVERY TEN YEARS

NOTIFICATION OF SERVICE REQUIREMENTS:

- Your next service is due in six (6) months or 7,500 miles (12,000 km), whichever is sooner.
- Please refer to your owner's manual for Service Recommendations if your vehicle is used extensively off-road, or under severe conditions.
- ◆ The owner or operator is responsible for **Owner Checks** listed in the Owner's Manual. These are not included in the Service Schedule.



MAINTENANCE SCHEDULE 1999 to 2002 DISCOVERY Series II

	IME (Months)	54	60	66	72	78	84	90	96
INTERVAL N	IILES (Thousands)	67.5	75	82.5	90	97.5	105	112.5	120
K	(ILOMETERS (Thousands)	108	120	132	144	156	168	180	192
VEHICLE EXTERIOR									
Add 16 oz Land Rover Fu	iel Conditioner (LRN5010)			0			0		
Inspect wiper blades						□			
Lubricate door locks, ch	 eck straps			î					
Lubricate hood latch and	d safety catch, fuel door hinges								
Replace Alarm handset	batteries								
VEHICLE INTERIOR									
Check parking brake (A	djust if necessary)								
Check seat belts									
UNDER HOOD						L			
Inspect coolant hoses		T		<u>-</u>	О	[Ι Τ	
Inspect radiator and AC	condenser								
Check power steering flu								l	
Clean battery and terming								l	
Inspect serpentine drive									
Replace serpentine driv								l	
Check brake fluid level						·			
Change brake fluid									
★ Replace air-cleaner element									
Change engine coolant									
★ Replace spark plugs									
UNDER VEHICLE						L		II	
★ Change engine oil and	d replace filter			0					
Perform body corrosion									
	condition and tread depth						<u> </u>		
Inspect tire pressures, c								-	
Inspect brake pads, can									
Inspect exhaust system	and near sinelus							 	
Lubricate drive shafts ar								l	
Inspect steering rods, jo									
Inspect shock absorbers								 	
Inspect snock absorbers									
	hment bolts for tightness								
	nsor and height sensor wiring								
Inspect fuel and hydraulic lines Change transfer gearbox oil							ك		
Change transmission flu						 		 	
Replace transmission flu									.
Check front and rear ax									
Change front and rear a									·
Inspect engine and trans									
Check steering box for f									
Service SLS filter (If equ								 	
Service SLS litter (If equ								 	ப
	Service in Passport to Service booklet								

* REQUIRED EMISSION MAINTENANCE SUPPLEMENTARY RESTRAINT SYSTEM (SRS): The AIR BAGS in the SRS must be replaced EVERY TEN YEARS

NOTIFICATION OF SERVICE REQUIREMENTS:

- ♦ Your next service is due in six (6) months or 7,500 miles (12,000 km), whichever is sooner.
- Please refer to your owner's manual for Service Recommendations if your vehicle is used extensively off-road, or under severe conditions.
- ◆ The owner or operator is responsible for **Owner Checks** listed in the Owner's Manual. These are not included in the Service Schedule.



MAINTENANCE SCHEDULE 1999 to 2002 DISCOVERY Series II

CAUTION: Do not perform two wheel roller tests.

Loaded I/M testing of permanent four wheel drive or traction control equipped vehicles must be conducted on a four wheel drive synchronized dynamometer. Otherwise a nonloaded test procedure must be followed.

\triangle	NOTE:	Mo)
	i-		

NOTE: Most items do not need to be carried out at every service. All required steps in a specific service are identified in the column headed by the mileage/month by a check box -

.

IMPORTANT

VEHICLES FITTED WITH SUPPLEMENTARY RESTRAINT SYSTEMS

- Seatbelt pre-tensioners (where fitted) and air bags must be replaced every TEN YEARS
- Side air bags (where fitted) must be replaced every FIFTEEN YEARS

IT IS RECOMMENDED THAT:

- At 90,000 miles (144,000 kilometers) or every six years, whichever is sooner, all hydraulic brake fluid, seals and hoses should be renewed.
- At 90,000 miles (144,000 kilometers) or every six years all working surfaces of the caliper cylinders should be examined and renewed where necessary.
- If a vehicle is used extensively in arduous/ off road conditions, the road wheel speed sensors, brake pads and calipers should be checked for abrasive wear every 1000 miles (1500 kilometers).
- If a vehicle is equipped with air suspension, and is used extensively in arduous/ off road conditions, the compressor inlet filter will require replacement at more regular intervals.
- The Power Steering/ ACE fluid reservoir should be replaced at 150,000 miles (250,000 kilometers)
- When the vehicle is used in dusty or off road conditions, or is subjected to deep wading, frequent replacement of the air cleaner may be required.

For full details regarding the operations contained in this maintenance check sheet, please refer to the Workshop Manual.